



Weldas CE markings on this product designates it as tested and certified according to directive 89/686/EEC Level 2.

Clothing type: *Fire Fox*TM

Trade mark: *Fire Fox*TM

Size: see imprint on the product

Sizing according to: EN ISO 13688 (in CM).



	CM
23-3615	46-68

Intended use:

General:

This product is intended to be used for all arc welding processes like MMA, MIG/MAG, TIG, micro plasma, spot and gas welding as well as plasma and oxygen cutting, gouging, brazing and thermal arc spraying. Because applications vary, it is the user's responsibility to identify the right product for each application.

Materials used:

305 gr/m² flame retardant fabric is used.

Identified hazards:

With the welding processes of intended use the following hazards are identified: flames, spatter of molten material, radiant heat as well as short term electrical shock.

Health information:

The pH, Chromium (VI) and PCP levels of all materials have been tested and meet CE health standards.
Coloring: coloring is done by using natural materials
As far as we know, this product does not contain any known allergic, carcinogenic or mutagenic substances.

High voltage:

This product protects against short term electrical shock and not against long term high voltages! Welding and cutting machines can cause these so follow the safety instructions of the machines used as well! When there is an increased risk of shock or electrical live parts additional electrical isolation will be required as is indicated under 6.10 of the EN11611 for protection against live electrical conductors up to 100 V = (DC).

Washing:

The flame retardant characteristics of the product will be valid for 5 washings at 40° C. No bleach or acid should be used, just standard washing detergents. A dimensional change can occur after washing. After cleaning, the clothing should be inspected.

Body protection in all positions:

This product protects in certain positions of working and welding. It could be possible that extra protection products are required. It is the responsibility of the user to identify that.

Drying and ironing:

Mechanical drying and ironing is possible but below 95° C.

Additional garments:

Additional garments shall meet at least Class 1 of the EN11611.



Storage: Store dry and at temperatures over 5° Celcius.
Do not stack higher than 5 cartons on 1 pallet.

Improper use:

Level of protection: The level of protection will be reduced if the welders protective clothing is contaminated with flammable materials.

Level of oxygen: Increase of oxygen in the air will reduce considerably the protection of the welders protective clothing against flame. Care should be taken when welding in confined places. Air enriched with oxygen will be dangerous!

Electrical isolation: The electrical isolation provided by the clothing will be reduced when the clothing is wet, dirty or soaked in sweat.

Use of 2-piece clothing:

When 2-piece clothing is used both items shall be worn together to provide the specified level of protection

Additional body protection during welding:

Additional body protection used with this product during welding must meet the appropriate EN standard for welding hazards.

Limitations for use:

This flame retardant cotton clothing to be used for general labour activities as well as welding.
User has to see to it that all closures are closed specially for use with welding applications and the choice of the right size. If molten metal stick to the clothing, the user needs to remove the clothing immediately. If the user observes symptoms similar to sunburn, UV radiation come through the product. In that case, the product needs to be repaired or replaced. The user should think about it that there might be more protective layers needed in the future.

Attention:

This product has been tested and certified at Centexbel (EU no. 0493). For more information on EN standards, testing methods, test reports, product certifications, and other products, please e-mail us at: europa@weldas.com or visit our web site: www.weldas.com

Remove:

Once this product can't be used anymore, it is the responsibility of the user to remove this product in an environmental way.

Warranty:

This product is warranted against manufacturing defects. If the product can be repaired, it needs to be done by the manufacturer.

Address information Weldas:

Weldas Europe B.V. Blankenweg 18 4612 RC Bergen op Zoom The Netherlands e-mail: europa@weldas.com



The following explains the pictogram marked on this product:



General safety requirements

Subclause	Requirement	Class 1	Class 2
6.1	Tensile strength - woven outer textile material - leather	400 N 80 N	400 N 80 N
6.2	Tear strength	20 N	20 N
6.3	Burst strength	200 kPa	200 kPa
6.4	Seam strength - textile material - leather	225 N 110 N	225 N 110 N
6.5	Dimensional change of woven textile materials Dimensional change of knitted textile materials	$\leq \pm 3 \%$ $\leq \pm 5 \%$	$\leq \pm 3 \%$ $\leq \pm 5 \%$
6.6	Requirements for leather: fat content	$\leq 15 \%$	$\leq 15 \%$
6.7	Flame spread	ISO 15025:2000, Procedure A (surface ignition); ISO 15025:2000, Procedure B (edge ignition); No flaming to the top or either side edge No hole formation ^a No flaming or molten debris Mean afterflame ≤ 2 s Mean afterglow ≤ 2 s	ISO 15025:2000, Procedure A (surface ignition); ISO 15025:2000, Procedure B (edge ignition); No flaming to the top or either side edge No hole formation ^a No flaming or molten debris Mean afterflame ≤ 2 s Mean afterglow ≤ 2 s
6.8	Impact of spatter	15 drops	25 drops
6.9	Heat transfer (radiation)	RHTI 24 W 7	RHTI 24 W 16
6.10	Electrical resistance	$> 10^5 \Omega$	$> 10^5 \Omega$
6.11	Innocuousness	See 6.11	See 6.11

^a For ISO 15025:2000, Procedure B, this requirement is not applicable

Testing and certification of this product is done according to EN ISO 11611:2015 by Centexbel, Technologiepark 7, 9052 Gent, Belgium (notified body number 0493).

Test report number 16.02513.01 and certificate number 031/2017/0253.

Test reports, certificates and manuals can be downloaded from: www.weldas-ce.com

